

B-8350 CMR

NEW

e▶ H.20


- Balastra con aletta per fissaggio spostato, regolabile. Optional supporti LED.
- Adjustable railing system, with side fixing. Optional LED supports.
- Verstellbares Railing System mit seitlicher Befestigung. Optional LED Auflage.





PAVIMENTO
LATERALE

COMPONENTI / COMPONENTS / EINZELTEILE







B-8350 + B-8001-CF2

- Profilo balastra + 2 Veleette
- Railing profile + 2 Cover profiles
- Profil für Geländer mit 2 Abdeckungen



B-SET-CMR-N-8 / B-SET-CMR-N-10 / B-SET-CMR-N-12

- Set morsetti e guarnizioni
- Set clamps and gaskets
- Set Klemmen und Dichtungen



xme605g

Set completo/mt L-3000/6000 mm Complete set/mt L = 3000/6000 mm Komplett-Set L-3000/6000 mm	FIN. FIN. OB.	Vetro Glass Glas	* Morsetti/mt Clamps/mt Klemmen/mt	Testato spinta Test side force Getestete Seitenkraft	Classe / Class / Klasse UNI11678:2017
B-8350-8	AN	8+8 1,52 pvb	2	150 kg	1 kN/m = 100 kg/m
B-8350-10	AN	10+10 1,52 pvb	2	300 kg	2 kN/m = 200 kg/m
B-8350-12	AN	12+12 1,52 pvb	3	450 kg	3 kN/m = 300 kg/m
^B-8350-G-8	GR	8+8 1,52 pvb	2	150 kg	1 kN/m = 100 kg/m
^B-8350-G-10	GR	10+10 1,52 pvb	2	300 kg	2 kN/m = 200 kg/m
^B-8350-G-12	GR	12+12 1,52 pvb	3	450 kg	3 kN/m = 300 kg/m

^ Profilo balastra grezzo senza velleette / Raw balustrade profile without cover profiles / Rohes Geländerprofil ohne Abdeckungen